



## NevoSwitch equipped with 5 QUAD inputs and 32 outputs

### When quality matters

Cascadable and quad compatible multiswitch, equipped with 5 inputs (one terrestrial, and the four polarities of one satellite) and 32 user outputs. Can be used as a terminal (star topology) or as a cascade by using a simple switch.

<b>Ref.</b>	714417
<b>Logical ref.</b>	MSUK532NCQ
<b>EAN13</b>	8424450187562

### Packing

<b>Box</b>	1 pcs.
------------	--------

### Physical data

<b>Net weight</b>	1,778.50 g
<b>Gross weight</b>	2,229.00 g
<b>Width</b>	137.00 mm
<b>Height</b>	120.00 mm
<b>Depth</b>	30.00 mm

### Highlights

- 12 V power supply (ref. 9916) included
- A 22 kHz tone can be generated, which makes it compatible with any LNB, including QUAD LNB.
- A switch for either powering terrestrial pre-amplifiers or allowing current circulation
- Remote power feeding using VL

- DC circulation from the inputs up
- Active terrestrial
- European design, quality, and manufacturing

## Main features

---

- Very compact
- Made of zamak
- Input and output colour identification
- Available ECO mode
- Selector switch to shift between cascade and terminal modes
- 12 V power supply
- Low power consumption

## Technical specifications : Ref. 714417

Number of inputs		5
Number of cascadable outputs		5
Number of user outputs		32
Frequency range TERR.	MHz	47 ... 862
Frequency range SAT.	MHz	950 ... 2400
Input level TERR.	dBµV	92
Input level SAT.	dBµV	105
Through losses TERR.	dB	9
Through losses SAT.	dB	6 ... 16
Tap losses 1...8 TERR.	dB	2
Tap losses 1...8 SAT.	dB	1
Tap losses 9...16 TERR.	dB	4
Tap losses 9...16 SAT.	dB	2
Tap losses 17...24 TERR.	dB	6
Tap losses 17...24 SAT.	dB	5
Tap losses 25...32 TERR.	dB	8
Tap losses 25...32 SAT.	dB	8
Isolation H/V	dB	> 30
Isolation users	dB	> 25
Powering	Vdc	12
Max. current (PSU)	mA	210
Max. current (STB)	mA	35
Operating temperature	°C	-5 ... 45
Protection index		20